

PO Box 14527, Wadeville 1422  
 180 - 181 Haring Road  
 Wadeville

Tel: (011) 827-5848  
 Fax: (011) 827-5832  
 E-mail: [oilflow@oilflow.co.za](mailto:oilflow@oilflow.co.za)  
[www.oilflow.co.za](http://www.oilflow.co.za)



## CVT Fully Synthetic

### Product Description

CVT oil is a multi-vehicle full synthetic service – fill fluid developed for the latest generation gear boxes to exceed the performance of the Asian original OEM (original equipment manufacturer) The balanced formulation incorporating special additive and selected base stocks for high torque capacity also ensures protection against foam forming, excellent anti-ageing and anti- oxidation properties.

### Features and Benefits

- CVT ensures smooth functioning of gears and excellent protection
- Maintain high steel-steel friction
- Superior anti-shudder durability for greater driving comfort to prevent unwanted slip in torque converter clutches
- Continuous variability properties allows the engine to maintain constant speed, and also optimal gear ratio.
- Maximized engine efficiency, resulting in improved fuel economy
- Provides tenacious oil film, good shear stability and maintain the oil pressure in the CVT system
- Excellent thermal and oxidation stability.

### Meets or exceeds the following industry specifications:

<ul style="list-style-type: none"> <li>• NISSAN NS -1, NS-2, XTRONIC TRANSMISSION</li> <li>• JATCO</li> <li>• ZF</li> <li>• MERCEDES 236.20</li> <li>• VOLVO 4959</li> <li>• FORD CVT 23</li> </ul>	<ul style="list-style-type: none"> <li>• GM SATURN DEX – CVT</li> <li>• EZL 799</li> <li>• SUZUKI TC</li> <li>• SUBARU</li> <li>• TOYOTA TC</li> <li>• VW</li> <li>• AUDI</li> </ul>
---	--

### Technical Data

Density @ 200C	0.854 kg/l
Viscosity @ 40°C	37 cSt
Viscosity @ 100°C	7 cSt
Viscosity Index	173
Flash Point °C	210
Pour Point °C	-52
Color	Yellow

