

Power Supply & Consumption	
Input Voltage	AC 110V~240V
Frequency	50/60Hz
Phase	AC INPUT
Power Consumption (Sound Bar)	30W
Power Consumption (Subwoofer)	30W
Power Consumption (Stand-by)	<0.5W
Performance Specifications	
Output Power (Sound Bar)	120W, 30W x 4 (@10%THD)
Output Power (Subwoofer)	80W (@10%THD)
Output Power (Total)	200W
Sound Bar (Frequency Response)	120Hz-20KHz
Woofer Speaker/ch (Size)	48 x 90mm
Woofer Speaker/ch (Impedance)	8ohm
Tweeter Speaker/ch (Size)	1.25"
Tweeter Speaker/ch (Impedance)	8ohm
Subwoofer (Frequency Response)	40Hz-120Hz
Subwoofer (Type)	Woofer
Subwoofer (Size)	6.5"
Subwoofer (Impedance)	4ohm
Key Components	
DSP	Sunplus 8109S-A
HDMI IC/Module	Sunplus 8109S-A
Wireless to Subwoofer	2.4G
Sound Enhancement	
Sound Mode	On, Off
Sound Mode	

Movie / Music / News
Decoder
Dolby Digital
√
PCM
√
MultichPCM
√
Others
WAV(48K) / WMA / MP3
Function Features
HDMI Type
HDMI 1.4
HDMI ARC
1
HDMI IR Pass Thru
HDMI CEC RC PASS THRU
Bluetooth
√
BT Version
BT 4.2
Auto Power On / Off (Auto wake)
On (Not for USB / BT) / Off (For all)
Wall Mountable
√
USB port
√
Control Key (On Sound Bar)
On / Standby
√
Input (source)
√
Volume +
√
Volume -
√
Terminals
HDMI
1, ARC only
Coaxial Input
1
Optical
1
Audio In (3.5mm)
1
USB
1, USB Audio and FW update
Remote Control
On / Standby (SB)

√
Volume +
√
Volume –
√
EQ (Sound Mode)
√
Mute
√
Input / Source
√
Bluetooth
√
Next [Navigation / BT / USB]
√
Previous [Navigation / BT / USB]
√
Play / Pause [BT / USB] PAIR [BT Pairing]
√
Surround
√
Dimmer+
√
Dimmer-
√
Bass+
√
Bass-
√
Total Keys QTY
15
Accessories
Operation Manual
1
Quick Guide
1
Wall Mount Angle
1
Wall Mount Guide
1
Remote Control
1
Battery
2
AC power cord
AAA x 2
Optical Cable (1.5mm)
1
Shipping Details
Sound Bar (Net weight (kg))

2
Sound Bar (Dimensions (WxDxH) mm)
960 x 58 x 82
Subwoofer (Net weight (kg))
5.5
Subwoofer (Dimensions (WxDxH) mm)
170 x 342 x 313