

## Specifications

Model name	CQ32G3SE
Panel	31.5" (VA / 1000R)
Pixel Pitch (mm)	0.2724 (H) × 0.2724 (V)
Effective Viewing Area (mm)	697.344 (H) × 392.256 (V)
Brightness (typical)	250 cd/m <sup>2</sup>
Contrast Ratio	3000 : 1 (Typical) 80 Million : 1 (DCR)
Response Time	1ms (MPRT) / 4ms (GtG)
Viewing Angle	178° (H) / 178° (V) (CR > 10)
Color Gamut	NTSC 102% (CIE1976) / sRGB 123% (CIE1931) / DCI-P3 93% (CIE1976)
Color Accuracy	Delta E < 2
Optimum Resolution	2560 × 1440 @ 165Hz – DisplayPort1.4 2560 × 1440 @ 144Hz – HDMI2.0
Display Colors	16.7 Million
Signal Input	HDMI 2.0 x 2, DisplayPort 1.4 x 1
HDCP Version	HDMI: 2.2, DisplayPort: 2.2
USB Hub	no
Power Supply	100 - 240V ~ 1.5A, 50 / 60Hz
Power Consumption (typical)	52W
Speakers	no
Line in & Earphone	Earphone
Wall-Mount	100mm x 100mm
Adjustable Stand	Tilt: -5° ~ 23°
Product without Stand (mm)	424.2 (H) × 700.5 (W) × 111.2 (D)
Product with Stand (mm)	523.7 (H) × 700.5 (W) × 263.8 (D)
Product without Stand (kg)	6.29
Product with Stand (kg)	7.02
Cabinet Color	Black & Red

---

Regulatory Approvals

RCM / MEPS / CE / CB / FCC / KC / KCC / e-Standby / BSMI

\* Design and specifications are subject to change  
without notice.