

Specifications

Model name	27G2
Panel	27" (IPS)
Pixel Pitch (mm)	0.3114 (H) x 0.3114 (V)
Effective Viewing Area (mm)	597.88 (H) x 336.31 (V)
Brightness (typical)	250 cd/m ²
Contrast Ratio	1000 : 1 (Typical) 80 Million : 1 (DCR)
Response Time	1ms (MPRT)
Viewing Angle	178° (H) / 178° (V) (CR > 10)
Color Gamut	NTSC 104% (CIE1976) / sRGB 118% (CIE1931) / DCI-P3 95% (CIE1976)
Color Accuracy	-
Optimum Resolution	1920 x 1080 @ 144Hz – DisplayPort, HDMI 1920 x 1080 @ 60Hz – VGA
Display Colors	16.7 Million
Signal Input	VGA x 1, HDMI 1.4 x 2, DisplayPort 1.2 x 1
HDCP Version	HDMI: 1.4, DisplayPort: 1.4
USB Hub	no
Power Supply	100 - 240V ~ 1.5A, 50 / 60Hz
Power Consumption (typical)	28W
Speakers	no
Line in & Earphone	-
Wall-Mount	100mm x 100mm
Adjustable Stand	Height: 130mm, Pivot: 0°~90° ± 2°, Swivel: -30° ~30°, Tilt: -5° ~ 23°
Product without Stand (mm)	363 (H) x 612.1 (W) x 46 (D)
Product with Stand (mm)	395.9~525.9 (H) x 612.1 (W) x 227.4 (D)
Product without Stand (kg)	3.7
Product with Stand (kg)	5.1
Cabinet Color	Black & Red

Regulatory Approvals

BSMI / KC / KCC / e-Standby / RCM / MEPS / CE / CB / FCC

* Design and specifications are subject to change
without notice.