

Specifications

Model name	24B2XHM
Panel	23.8" (VA)
Pixel Pitch (mm)	0.2745 (H) × 0.2745 (V)
Effective Viewing Area (mm)	527.04 (H) × 296.46 (V)
Brightness (typical)	250 cd/m ²
Contrast Ratio	3000 : 1 (Typical) 20 Million : 1 (DCR)
Response Time	6ms (GtG (BW))
Viewing Angle	178° (H) / 178° (V) (CR > 10)
Color Gamut	NTSC 80% (CIE1976) / sRGB 101% (CIE1931)
Color Accuracy	-
Optimum Resolution	1920 × 1080 @ 75Hz – HDMI 1920 × 1080 @ 60Hz – VGA
Display Colors	16.7 Million
Signal Input	VGA × 1, HDMI 1.4 × 1
HDCP Version	-
USB Hub	no
Power Supply	19V DC, 1.31A
Power Consumption (typical)	21W
Speakers	no
Line in & Earphone	-
Wall-Mount	100mm × 100mm
Adjustable Stand	Tilt: -5° ~ 20°
Product without Stand (mm)	320.94 (H) × 539.47 (W) × 37.6 (D)
Product with Stand (mm)	418.35 (H) × 539.47 (W) × 170.94 (D)
Product without Stand (kg)	2.41
Product with Stand (kg)	2.73
Cabinet Color	Black
Regulatory Approvals	CE / FCC

* Design and specifications are subject to change without notice.