Parrot Products (Pty) Ltd Whiteboard Cleaner Material Safety Data Sheet Emergency Telephone Number +27 11 607 7600

1.0	Identification of the Substance / Preparation and of the company / undertaking						
1.1	Product Name	Parrot Product	Parrot Products Office Equipment & Whiteboard Cleaner				
1.2	Intended use	Office Equipment and Whiteboard Cleaner					
1.3	Supplier / Manufacturer Address	Parrot Products (Pty) Ltd 22 Cleveland Road Cleveland Johannesburg South Africa					
1.4	Emergency Tel:	+27 (0)11 607 7600					
	Fax Number	+27 (0)11 615	+27 (0)11 615 2502				
	e-mail	sales@parrot	sales@parrot.co.za				
3.0	Hazards Identification						
3.1	Preparation Classification	This preparation may be hazardous under 67/548/EEC and 1999/45/EC regulations as amended. This preparation requires a safety data sheet in accordance with 91/155/EC as amended. Additional information relating to health and environmental hazards can be found in Sections 11 and 12 of this safety data sheet.					
3.2	Danger Symbols:	F, Xi					
3.3	Phrases –R–	R11, R 20/21/2	22. R36/38. F	67	minimus succession in the succ	эн э	
3.4	Danger Identification	HIGHLY FLAMMABLE. HARMFUL BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED. IRRITATING TO EYES AND SKIN					
2.0							
	Contains:	EINECS	CAS	Conc'n %	Symbols	R-phrases	
	Water	-	-	Approx 1%	-	-	
	Iso Propyl	-	67-63-0	97%	F, Xi	R11, R36, R67	
	Fatty Acid Ester, surfactants	various	various	2%		None, but see attached MSDS for Multichem Board Conditioner	
Note:	The complete text of risk -R- p	hrases can be fo	ound in Section	on 15 and 16			
4.0	First Aid Measures						
	Route	First Aid					
4.1	Skin Contact		Remove any contaminated clothing. Wash with soap. If irritation occurs consult a physician.				
4.2	Eye Contact		Irrigate with a suitable eye solution or water - obtain medical attention.				
4.3	Inhalation	Remove from	Remove from exposure - in severe cases obtain medical attention.				
4.4	Ingestion	Give plenty to	Give plenty to drink if ingestion is suspected. DO NOT induce vomiting and consult a physician.				

es e
Flash Point: 12°C (Closed Cup)
Explosive Limits: Lower limit 3.5% to 19% upper limit.
Alcohol resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand
or earth may be used for small fires only. Water may not be effective initially.
Reacts strongly with oxidisers.
Carbon Monoxide (CO) can form with incomplete combustion. Some oxides of
nitrogen (NO _x) and sulphur (SO _x) could be formed. Complete combustion will yield
primarily carbon dioxide (CO ₂) and water.
Fire fighters should wear proper protective equipment and self-contained breathing
apparatus with full face-piece.
Vapours may flow along surfaces to distant ignition sources and flash back. Closed
containers exposed to heat may explode. Move exposed containers from fire area if it
can be done without risk. Use water to keep fire-exposed containers cool.
easures
Avoid contact with skin and eyes. Ventilate contaminated area thoroughly. Do not
breathe vapour. Extinguish naked flames. Remove ignition sources. No smoking.
Avoid sparks. Evacuate the area of all non-essential personnel. Shut off leaks, if
possible without personal risk.
Prevent contamination of soil and water. Prevent from spreading or entering into
drains, ditches or rivers by using sand, earth, or other appropriate barriers.
Absorb or contain liquid with sand, earth or spill control material. Collect avoiding
possible spark ignition and place in a labelled, sealable container for subsequent safe
disposal. Put leaking containers in a labelled drum. Solvent is miscible with water.
Flush contaminated area with plenty of water. Retain washings as contaminated
waste. Refer to Sections 8.0 and 13.0 for additional information on exposure and
disposal.
Description of the second of t
Product is not intended nor should be allowed to maintain prolonged skin contact.
Ensure good ventilation or the provision of local exhaust ventilation where possible.
Avoid contact with eyes plain and elething evoid ingestion and inhelation. Avoid
Avoid contact with eyes, skin and clothing, avoid ingestion and inhalation. Avoid
sources of Ignition.
sources of Ignition. Keep away from direct sunlight and other sources of heat or ignition. Keep away from
sources of Ignition. Keep away from direct sunlight and other sources of heat or ignition. Keep away from oxidising agents. Do not smoke in storage areas. Keep container tightly closed and in
sources of Ignition. Keep away from direct sunlight and other sources of heat or ignition. Keep away from oxidising agents. Do not smoke in storage areas. Keep container tightly closed and in a well-ventilated place.
sources of Ignition. Keep away from direct sunlight and other sources of heat or ignition. Keep away from exidising agents. Do not smoke in storage areas. Keep container tightly closed and in a well-ventilated place. Low flash point; requires attention to equipment used in transport and use so as to
Sources of Ignition. Keep away from direct sunlight and other sources of heat or ignition. Keep away from oxidising agents. Do not smoke in storage areas. Keep container tightly closed and in a well-ventilated place. Low flash point; requires attention to equipment used in transport and use so as to avoid sparks and other sources of ignition. Take precautionary measures against
Sources of Ignition. Keep away from direct sunlight and other sources of heat or ignition. Keep away from exidising agents. Do not smoke in storage areas. Keep container tightly closed and in a well-ventilated place. Low flash point; requires attention to equipment used in transport and use so as to avoid sparks and other sources of ignition. Take precautionary measures against static discharges. Earth all equipment. Avoid splash filling. Do not empty into drains.
Sources of Ignition. Keep away from direct sunlight and other sources of heat or ignition. Keep away from exidising agents. Do not smoke in storage areas. Keep container tightly closed and in a well-ventilated place. Low flash point; requires attention to equipment used in transport and use so as to avoid sparks and other sources of ignition. Take precautionary measures against static discharges. Earth all equipment. Avoid splash filling. Do not empty into drains. Personal Protection
Sources of Ignition. Keep away from direct sunlight and other sources of heat or ignition. Keep away from exidising agents. Do not smoke in storage areas. Keep container tightly closed and in a well-ventilated place. Low flash point; requires attention to equipment used in transport and use so as to avoid sparks and other sources of ignition. Take precautionary measures against static discharges. Earth all equipment. Avoid splash filling. Do not empty into drains. Personal Protection Ethyl Alcohol EH40 (UK)
Keep away from direct sunlight and other sources of heat or ignition. Keep away from exidising agents. Do not smoke in storage areas. Keep container tightly closed and in a well-ventilated place. Low flash point; requires attention to equipment used in transport and use so as to avoid sparks and other sources of ignition. Take precautionary measures against static discharges. Earth all equipment. Avoid splash filling. Do not empty into drains. Personal Protection Ethyl Alcohol EH40 (UK) OES: 1000 ppm Period: 8 hours
Sources of Ignition. Keep away from direct sunlight and other sources of heat or ignition. Keep away from exidising agents. Do not smoke in storage areas. Keep container tightly closed and in a well-ventilated place. Low flash point; requires attention to equipment used in transport and use so as to avoid sparks and other sources of ignition. Take precautionary measures against static discharges. Earth all equipment. Avoid splash filling. Do not empty into drains. Personal Protection Ethyl Alcohol EH40 (UK)
Keep away from direct sunlight and other sources of heat or ignition. Keep away from exidising agents. Do not smoke in storage areas. Keep container tightly closed and in a well-ventilated place. Low flash point; requires attention to equipment used in transport and use so as to avoid sparks and other sources of ignition. Take precautionary measures against static discharges. Earth all equipment. Avoid splash filling. Do not empty into drains. Personal Protection Ethyl Alcohol EH40 (UK) OES: 1000 ppm Period: 8 hours
Keep away from direct sunlight and other sources of heat or ignition. Keep away from oxidising agents. Do not smoke in storage areas. Keep container tightly closed and in a well-ventilated place. Low flash point; requires attention to equipment used in transport and use so as to avoid sparks and other sources of ignition. Take precautionary measures against static discharges. Earth all equipment. Avoid splash filling. Do not empty into drains. Personal Protection Ethyl Alcohol EH40 (UK) OES: 1000 ppm Period: 8 hours OES: 1900 mg/m³ /period: 8 hours
Keep away from direct sunlight and other sources of heat or ignition. Keep away from oxidising agents. Do not smoke in storage areas. Keep container tightly closed and in a well-ventilated place. Low flash point; requires attention to equipment used in transport and use so as to avoid sparks and other sources of ignition. Take precautionary measures against static discharges. Earth all equipment. Avoid splash filling. Do not empty into drains. Personal Protection Ethyl Alcohol EH40 (UK) OES: 1000 ppm Period: 8 hours OES: 1900 mg/m³ /period: 8 hours
Sources of Ignition. Keep away from direct sunlight and other sources of heat or ignition. Keep away from oxidising agents. Do not smoke in storage areas. Keep container tightly closed and in a well-ventilated place. Low flash point; requires attention to equipment used in transport and use so as to avoid sparks and other sources of ignition. Take precautionary measures against static discharges. Earth all equipment. Avoid splash filling. Do not empty into drains. Personal Protection Ethyl Alcohol EH40 (UK) OES: 1000 ppm Period: 8 hours OES: 1900 mg/m³ /period: 8 hours EH40 (UK 2005) skin: TWA: 25 ppm STEL: 50 ppm
Sources of Ignition. Keep away from direct sunlight and other sources of heat or ignition. Keep away from oxidising agents. Do not smoke in storage areas. Keep container tightly closed and in a well-ventilated place. Low flash point; requires attention to equipment used in transport and use so as to avoid sparks and other sources of ignition. Take precautionary measures against static discharges. Earth all equipment. Avoid splash filling. Do not empty into drains. Personal Protection Ethyl Alcohol EH40 (UK) OES: 1000 ppm Period: 8 hours OES: 1900 mg/m³ /period: 8 hours EH40 (UK 2005) skin: TWA: 25 ppm STEL: 50 ppm Avoid inhalation of the vapours when the product in being used. Local exhaust
Sources of Ignition. Keep away from direct sunlight and other sources of heat or ignition. Keep away from oxidising agents. Do not smoke in storage areas. Keep container tightly closed and in a well-ventilated place. Low flash point; requires attention to equipment used in transport and use so as to avoid sparks and other sources of ignition. Take precautionary measures against static discharges. Earth all equipment. Avoid splash filling. Do not empty into drains. Personal Protection Ethyl Alcohol EH40 (UK) OES: 1000 ppm Period: 8 hours OES: 1900 mg/m³ /period: 8 hours EH40 (UK 2005) skin: TWA: 25 ppm STEL: 50 ppm Avoid inhalation of the vapours when the product in being used. Local exhaust ventilation (LEV) should be used in conjunction with other control measures as a means of removing material accidentally released. Type approved RPE for organic vapours if required.
Sources of Ignition. Keep away from direct sunlight and other sources of heat or ignition. Keep away from poxidising agents. Do not smoke in storage areas. Keep container tightly closed and in a well-ventilated place. Low flash point; requires attention to equipment used in transport and use so as to avoid sparks and other sources of ignition. Take precautionary measures against static discharges. Earth all equipment. Avoid splash filling. Do not empty into drains. Personal Protection Ethyl Alcohol EH40 (UK) OES: 1000 ppm Period: 8 hours OES: 1900 mg/m³ /period: 8 hours EH40 (UK 2005) skin: TWA: 25 ppm STEL: 50 ppm Avoid inhalation of the vapours when the product in being used. Local exhaust ventilation (LEV) should be used in conjunction with other control measures as a means of removing material accidentally released. Type approved RPE for organic
Sources of Ignition. Keep away from direct sunlight and other sources of heat or ignition. Keep away from oxidising agents. Do not smoke in storage areas. Keep container tightly closed and in a well-ventilated place. Low flash point; requires attention to equipment used in transport and use so as to avoid sparks and other sources of ignition. Take precautionary measures against static discharges. Earth all equipment. Avoid splash filling. Do not empty into drains. Personal Protection Ethyl Alcohol EH40 (UK) OES: 1000 ppm Period: 8 hours OES: 1900 mg/m³ /period: 8 hours EH40 (UK 2005) skin: TWA: 25 ppm STEL: 50 ppm Avoid inhalation of the vapours when the product in being used. Local exhaust ventilation (LEV) should be used in conjunction with other control measures as a means of removing material accidentally released. Type approved RPE for organic vapours if required.
Sources of Ignition. Keep away from direct sunlight and other sources of heat or ignition. Keep away from oxidising agents. Do not smoke in storage areas. Keep container tightly closed and in a well-ventilated place. Low flash point; requires attention to equipment used in transport and use so as to avoid sparks and other sources of ignition. Take precautionary measures against static discharges. Earth all equipment. Avoid splash filling. Do not empty into drains. Personal Protection Ethyl Alcohol EH40 (UK) OES: 1000 ppm Period: 8 hours OES: 1900 mg/m³ /period: 8 hours EH40 (UK 2005) skin: TWA: 25 ppm STEL: 50 ppm Avoid inhalation of the vapours when the product in being used. Local exhaust ventilation (LEV) should be used in conjunction with other control measures as a means of removing material accidentally released. Type approved RPE for organic vapours if required. Protective butyl rubber gloves.
Sources of Ignition. Keep away from direct sunlight and other sources of heat or ignition. Keep away from oxidising agents. Do not smoke in storage areas. Keep container tightly closed and in a well-ventilated place. Low flash point; requires attention to equipment used in transport and use so as to avoid sparks and other sources of ignition. Take precautionary measures against static discharges. Earth all equipment. Avoid splash filling. Do not empty into drains. Personal Protection Ethyl Alcohol EH40 (UK) OES: 1000 ppm Period: 8 hours OES: 1900 mg/m³ /period: 8 hours EH40 (UK 2005) skin: TWA: 25 ppm STEL: 50 ppm Avoid inhalation of the vapours when the product in being used. Local exhaust ventilation (LEV) should be used in conjunction with other control measures as a means of removing material accidentally released. Type approved RPE for organic vapours if required. Protective butyl rubber gloves. Safety goggles or face shield.
Sources of Ignition. Keep away from direct sunlight and other sources of heat or ignition. Keep away from direct sunlight and other sources of heat or ignition. Keep away from direct sunlight and other sources. Keep container tightly closed and in a well-ventilated place. Low flash point; requires attention to equipment used in transport and use so as to avoid sparks and other sources of ignition. Take precautionary measures against static discharges. Earth all equipment. Avoid splash filling. Do not empty into drains. Personal Protection Ethyl Alcohol EH40 (UK) OES: 1000 ppm Period: 8 hours OES: 1900 mg/m³ /period: 8 hours EH40 (UK 2005) skin: TWA: 25 ppm STEL: 50 ppm Avoid inhalation of the vapours when the product in being used. Local exhaust ventilation (LEV) should be used in conjunction with other control measures as a means of removing material accidentally released. Type approved RPE for organic vapours if required. Protective butyl rubber gloves. Safety goggles or face shield. Overalls and anti static safety shoes.

Rev No: 01 Issue Date: 06/01/2015 Page 2 of 4

9.0	Physical and Chemical Properties						
	Odour	Characteristic, Ethereal.					
	Appearance	Colourless					
	Volatility	Volatile liquid					
	pH	-					
	Boiling Point / Range	78.3℃					
	Flash Point	12℃					
	Auto-ignition	365℃					
	Explosive Properties	This preparation is not considered explosive.					
	Explosive Limits: Explosive Limits: Lower limit 3.5% to 19% upper limit.						
	Vapour Pressure	-					
	Relative Density	-					
	Solubility	Water solubility – solvents miscible with water.					
	Viscosity						
10.0	Stability and Reactive	ity					
10.1	Conditions to Avoid	Considered a stable product. Static discharge.					
10.2	Materials to Avoid	Oxidising agents and bases.					
	Hazardous	May give of irritant / toxic fumes if involved in a fire. Primarily forms oxides of carbon					
10.3	Decomposition	during combustion.					
11.0	Toxicological Informa						
11.1	Acute Effects						
	Vapour inhalation	Ataxia, confusion, dizziness, drowsiness, headache, nausea, weakness.					
	Skin	De-fatting of skin. Dry skin. Note that dermal absorption of solvents could also contribute substantially to the total body burden.					
	Eyes	Irritant. Lacrimation, redness, pain, blurred vision.					
	Ingestion	Abdominal pain, sore throat, drowsiness, headache, nausea.					
11.2	Target Organ Effects	The preparation may cause liver and kidney damage if abused.					
11.3	Sensitisation	Allergic skin reaction / dermatitis could occur with misuse of this preparation.					
12.0	Ecological Information	on					
12.1	Ecotoxicity	Prevent contamination of soil and water. Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.					
12.2	Mobility	Mobile liquid. Do not allow to contaminate water courses or soils.					
12.3	Persistence and Degradability						
12.4	Bio accumulative Potential	This product shows a low bioaccumulation potential.					
12.5	Other Adverse Effects						
13.0	Disposal Considerati						
waste	Dispose of spilled material and containers in accordance with state and local regulations for hazardous or 'Special' waste. Consider recycling or incineration. State or local regulations are complex and subject to change so should be						
14.0	sulted by the owner of the waste prior to disposal. Transport Information						
	UN No:	1993					
	Proper Shipping Name:	Flammable Liquid n.o.s (Contains Ethanol)					
	ADR, IATA, IMDG Hazard Class	3					
	Packing Group	2					

15.0	Regulatory Informa	ition				
15.1	Hazard Symbols	F	Xn			
		HIGHLY FLAMMABLE	HARMFUL			
15.2	-R-phrases					
	R11	HIGHLY FLAMMABLE				
	R20/21/22	HARMFUL BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED				
	R36/38	IRRITATING TO EYES AND SKIN				
	R67	VAPOURS MAY CAUSE DROWSINESS AND DIZZINES				
15.3	-S-Phrases					
	S2	KEEP OUT OF THE REACH OF CHILDRE	N			
	S7	KEEP CONTAINER TIGHTLY CLOSED				
	S16	KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING WEAR SUITABLE PROTECTIVE CLOTHING AND GLOVES				
	S36/37					
	S46	IF SWALLOWED SEEK MEDICAL ADV	ICE IMMEDIATELY AND SHOW THIS			
16.0	Other information					
16.1	Select Bibliography	Regulation 67/548/EEC Regulation 91/155/CE Regulation 1999/45/CE Regulation 2001/58/CE Regulation 2001/59/CE Regulation 2001/60/CE				
16.2	HS Tariff No:	321590 10				
16.3	The information containe safety legislation. The al	bed herein does not constitute the user's own assessment of workplace risk as required by other health and bove information is provided in good faith and is based on our present knowledge. It shall not constitute a product feature and shall not establish a legally valid contractual arrangement.				